


SFGH WM4 C BT



WM4 C PHOTOVOLTAIC CONNECTORS

- One crimp contact for 4mm² and 6mm² cables.
- TÜV approval according to the latest standard DIN EN 50521.
- Can be loaded with a rated current of up to 35A.

GENERAL ORDERING DATA	
Type	SFGH WM4 C BT
Order No.	1530700000
Version	Photovoltaics, Plug-in connector, Pin
GTIN (EAN)	4050118335330
Qty.	100 pc(s).

TECHNICAL DATA		
DIMENSIONS AND WEIGHTS	Net weight	13.8g
TECHNICAL DATA	Approvals	TÜV (DIN EN 50521)
	Cable type	2 Pfg1169/08.07, EN 50618:2014
	Conductor cross-section, max.	6mm ²
	Conductor cross-section, min.	4mm ²
	External thread	M 16
	Outer cable diameter, max.	7mm
	Outer cable diameter, min.	5.5mm
	Pollution severity	2
	Protection degree	IP65, IP67, IP2x open
	Rated current	35A
Rated voltage	1500V DC (IEC)	
CLASSIFICATIONS	ETIM 6.0	EC002928
	ETIM 7.0	EC002928
	eClass 9.0	22-57-92-03
	eClass 9.1	27-44-01-07
	eClass 10.0	27-44-01-07
APPROVALS	Approvals	
	ROHS	Conform
DOWNLOADS	Engineering Data	EPLAN_WSCAD
	Engineering Data	STEP
	User Documentation	BPZL_WM4CL